

L4 ANSWER 439 OF 561 CA COPYRIGHT 2004 ACS on STN

AN 100:86711 CA

ED Entered STN: 12 May 1984

TI Phenolic resin compositions

PA Sumitomo Bakelite Co., Ltd., Japan

SO Jpn. Kokai Tokkyo Koho, 4 pp.

CODEN: JKXXAF

DT Patent

LA Japanese

IC C08L061-06; C08K003-22; C08K003-30; C08K005-20

CC 37-6 (Plastics Manufacture and Processing)

FAN.CNT 1

	PATENT NO.	KIND	DATE	APPLICATION NO.	DATE
PI	JP 58149939	A2	19830906	JP 1982-30605	19820301
	JP 62055550	B4	19871120		
PRAI	JP 1982-30605		19820301		

AB Al(OH)3 can be added as a flame retardant to phenolic resol compn. without interfering with the crosslinking reaction if it is combined with gypsum in a ratio of 0.5-0.40:1. Resol phenolic resin 100, water 10, gypsum 100, Al(OH)3 15, and 60% aq.

p-toluenesulfonic acid curing catalysts 15 parts were mixed and applied to a 300-g/m2 glass fiber mat, left overnight at 15.degree., then heated to 50.degree. for 2 h to obtain a reinforced plate .apprx.3-mm thick, which past the Japanese Transport Ministry flammability test.

ST aluminum hydroxide fireproofers phenolic resin; resol

flame retardant aluminum hydroxide; gypsum

aluminum hydroxide flame retardant; calcium

sulfate aluminum hydroxide fireproofers

IT Fireproofing agents

(aluminum hydroxide-gypsum mixts., for